



Introduction

Atлона LinkConnect™ H2H High Speed HDMI to HDMI cables provide reliable, consistent AV performance, and come with an Atлона Advantage lifetime warranty. The LinkConnect family of cables includes a comprehensive range of options for connector type, length, and budget, so it's easy to customize to fit any application.

Designed to work with the Pocket 3H (AT-PKT-3H) tabletop cable access enclosure and an Atлона switcher installed below the table, LinkConnect H2H cables offer you the right length to minimize excess cable. This combination helps ensure a clean, uncluttered meeting space minimizing in-room cable issues.

Key Features

Installation made easy

- LinkConnect cables can be ordered with other Atлона equipment and arrive onsite together.
- Single source supplier minimizes installation delays and ensures compatibility.

Available in 1, 2, and 3 meter (3.3, 6.6, and 9.8 feet) lengths

- Get the cable length you need for your specific installation.
- Provide an uncluttered, tangle-free meeting room or workspace.

Locking HDMI connector

- Ensure a secure cable connection to compatible Atлона equipment.
- Eliminate errors due to improperly connected cables.

Specifications

Video	
Signal	Input - HDMI Output - HDMI
Bandwidth	18 Gbps
UHD/HD/SD	4096x2160@60/50/30/25/24Hz 720p@60/59.94/50Hz 3840x2160@60/50/30/25/24Hz 576p@50Hz 1920x1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 576i@25Hz 1920x1080i@30/29.97/25Hz 480p@60/59.96Hz 480i@30Hz
VESA All resolutions are 60Hz	2560x2048 1366x768 2560x1600 1360x768 2048x1536 1280x1024 1920x1200 1280x800 1680x1050 1280x768 1600x1200 1152x768 1600x900 1024x768 1440x900 800x600 1400x1050 640x480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit

Audio			
HDMI Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Cable			
Length	Feet	Meters	
	AT-LC-H2H-1	3.3	1
	AT-LC-H2H-2	6.6	2
	AT-LC-H2H-3	9.8	3
Shielding	Triple Shielded		
Diameter	Inches	Millimeters	
	AT-LC-H2H-1	0.18	4.5
	AT-LC-H2H-2	0.18	4.5
	AT-LC-H2H-3	0.24	6
Jacket Material	PVC		
Conductor	AT-LC-H2H-1		34 AWG
	AT-LC-H2H-2		34 AWG
	AT-LC-H2H-3		30 AWG
	Connector		Gold-plated
Screw	M3*0.5mm		
Bend Radius	100mm		
Fire Rating	CL2		

Copyright, Trademark, and Registration

© 2025 Atлона Inc. All rights reserved. "Atлона" and the Atлона logo are registered trademarks of Atлона Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).