

Large Venue Vibration Isolating Coupler, Black **SKU: CMA348**



The CMA Large Venue Vibration Isolating Coupler reduces image movement caused by common building vibrations like HVAC, foot traffic, road traffic and doors shutting. The patented design works as a projector mount vibration isolator by connecting two Chief CMS columns (1.5" NPT) and limiting vibrations that are transmitted to the lower column. The CMA348 is for systems between 35-100 lbs (45.4 kg)

- Systems include all weight below the vibration isolator, including column, projector mount and projector
- Average weights of common mounts include: RPAU (4 lbs or 1.8 kg), RPMAU (5 lbs or 2.3 kg), and VCMU (33 lbs or 15 kg).
- Average weight of CMS columns under 12" in length are 1 lb (0.5 kg) or less

Compatible with Chief CMS columns (1.5" NPT)

Compatible with custom mounts (See MountFinder™)

Connects two extension columns; patented design isolates vibration transmitted to lower column to reduce image movement

Specifications

Dimensions & Measurements	Depth	58.42 cm (23 in)
	Height	15.24 cm (6 in)
	Overall Dimensions	6" x 23" x 23" (152 x 584 x 584 mm)
	Shipping Weight	12.21 kg (26.9 lbs)
	Weight Capacity	35-100 lbs (15.9 – 45.4 kg)
	Width	58.42 cm (23 in)
Characteristics & Features	Accessory Type	• Extension • Power
	Application	Ceiling
	Color	Black
	Special Features	• Large Venue • Vibration Dampening
	TAA Compliant	No
	UPC	841872172521

Source: <https://www.legrandav.com/products/accessories/projector-accessories/large-venue-vibration-isolating-coupler/cma348>