


Large Venue Vibration Isolating Coupler, White **SKU: CMA348W**



The CMA Large Venue Vibration Isolating Coupler reduces image movement caused by common building vibrations like HVAC, foot traffic, road traffic and doors shutting. The patented design works as a projector mount vibration isolator by connecting two Chief CMS columns (1.5" NPT) and limiting vibrations that are transmitted to the lower column. The CMA348 is for systems between 35-100 lbs (45.4 kg)

- Systems include all weight below the vibration isolator, including column, projector mount and projector
- Average weights of common mounts include: RPAU (4 lbs or 1.8 kg), RPMAU (5 lbs or 2.3 kg), and VCMU (33 lbs or 15 kg).
- Average weight of CMS columns under 12" in length are 1 lb (0.5 kg) or less

Compatible with Chief CMS columns (1.5" NPT)

Compatible with custom mounts (See MountFinder™)

Connects two extension columns; patented design isolates vibration transmitted to lower column to reduce image movement

Specifications

Dimensions &

Measurements

Depth	58.42 cm (23 in)
Height	15.24 cm (6 in)
Overall Dimensions	6" x 23" x 23" (152 x 584 x 584 mm)
Shipping Weight	11.54 kg (25.5 lbs)
Weight Capacity	35-100 lbs (15.9 – 45.4 kg)
Width	58.42 cm (23 in)

Characteristics & Features

Accessory Type	<ul style="list-style-type: none">• Extension• Power
Application	Ceiling
Color	White
Special Features	<ul style="list-style-type: none">• Large Venue• Vibration Dampening
TAA Compliant	No
UPC	841872172538

Source: <https://www.legrandav.com/products/accessories/projector-accessories/large-venue-vibration-isolating-coupler/cma348w>