

SFOL173L-10

DATA SHEET
FOL L Line



FOL L Line · Foldable Motorized Monitors

Foldable Motorized Monitors for boardroom and meeting room tables.
70° tilt adjustment that can be set according to user preferences.



SFOL173L-10

SOLTEC TECHNICAL SPECIFICATIONS

FOLDABLE MOTORIZED MONITOR FOL L Line

GENERAL DESCRIPTION

Foldable Motorized Monitor for boardroom and meeting room tables. 70° **tilt adjustment** that can be set according to user preference. High-end painted steel monitor housing.

DVI-D input.


RS-232 serial control through DB9 connector.

RS-485/422 serial control through RJ45 connector in loop and addressing.


Touch Screen



USB



Microphone



Channel Selector



Full HD Panel



Voting System



Full range of options available.



DISPLAY

Panel Technology	Edge LED Technology
Display Area (mm)	381.88(H) x 214.81(V)
Size	17.3"
Pixel Pitch (mm)	0.198 x 0.198
Screen Aspect	16:9
Native Resolution	1.920 x 1.080
Viewing Angle UDLR	60°/80°/80°/80°
Contrast Ratio	600:1 (Typ)
Brightness cd/m2	400 (Typ)
Colors	16.7M Colors
Response Time	40ms Ton + Toff
Life Time (hours)	50.000
Protective Glass	3mm with black border

CONNECTIVITY

Digital Input	1xDVI-D
RS-232 Control	1xDB9
RS-485/422 Control	2xRJ45 (With Loop)

CONTROL

Remote Control	1xRS232, 1xRS485/422
Manual Control	1 Pushbuttons (Up/Down) 2 Pushbuttons (Tilt adjustment)

ELECTRICAL

Power Adaptor	90 ~ 264VAC to 12VDC 47 ~ 63Hz
Power Consumption	30W
Energy Management	VESA DPMS

MECHANICAL (SFOL173L-10)

Screen (mm)	450 x 272
On-table Cover Plate (mm)	TBD
Under-table Housing (mm)	TBD
NET Weight (Kg)	TBD
Packaging dimensions (mm)	TBD
Gross Weight (Kg)	TBD

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 70°
Storage Temperature	-20° to 70°
Operation Humidity (%)	5 to 95
Storage Humidity (%)	5 to 95

OTHERS

Certifications	CE, RoHS, BIS, EAC, CB IECCE
Plug & Play	VESA DDC2Bi
Accessories	Mains Power Cord User Manual

ORDERING INFORMATION

SFOL173L-10	Standard 17.3" FOL L Line
SFOL173L-15B	Built-in Bosch Mic Delegate
SFOL173L-15BC	Built-in Bosch Mic Chairman
SFOL173L-15D	Built-in DIS/Shure Mic Delegate
SFOL173L-15DC	Built-in DIS/Shure Mic Chairman
SFOL173L-15T	Built-in Televic Mic Delegate
SFOL173L-15TC	Built-in Televic Mic Chairman
SFOL173L-15XLR	Built-in Generic XLR3 Mic

* Double microphone models: -16 instead of -15

Specifications subject to change without prior notice

