

# SFOL156G-10

DATA SHEET

FOL G Line



## FOL G Line · Foldable Motorized Monitors

Elegant and high-end Foldable Motorized Monitors for boardroom tables made of anodized aluminium housing. Protective glass with black border serigraphy.



# SFOL156G-10

## SOLTEC

### TECHNICAL SPECIFICATIONS

## FOLDABLE MOTORIZED MONITOR

### FOL G Line

## GENERAL DESCRIPTION

Foldable Motorized Monitor for boardroom and meeting room tables. 20° **tilt adjustment** that can be set according to user preference. High-end anodized aluminium monitor housing. Protective glass with black border serigraphy.

VGA and DVI-D inputs.


RS-232 serial control through DB9 connector.

RS-485/422 serial control through RJ45 connector in loop and addressing.

Touch Screen



USB



Keyboard



Channel Selector



Voting System



HDBaseT Input



Full range of options available.



## DISPLAY

|                     |                       |
|---------------------|-----------------------|
| Panel Technology    | Edge LED Technology   |
| Display Area (mm)   | 344.23(H) x 193.53(V) |
| Size                | 15.6"                 |
| Pixel Pitch (mm)    | 0.252 x 0.252         |
| Screen Aspect       | 16:9                  |
| Native Resolution   | 1.366 x 768           |
| Viewing Angle UD/LR | 80°/80°/85°/85°       |
| Contrast Ratio      | 500:1 (Typ)           |
| Brightness cd/m2    | 300 (Typ)             |
| Colors              | 16.7M Colors          |
| Response Time       | 8ms Ton + Toff        |
| Life Time (hours)   | 50.000                |
| Protective Glass    | 3mm with black border |

## CONNECTIVITY

|                    |                    |
|--------------------|--------------------|
| Analogue RGB Input | 1xDB15             |
| Digital Input      | 1xDVI-D            |
| RS-232 Control     | 1xDB9              |
| RS-485/422 Control | 2xRJ45 (With Loop) |

## CONTROL

|                |                                                            |
|----------------|------------------------------------------------------------|
| Remote Control | 1xRS232, 1xRS485/422                                       |
| Manual Control | 2 Pushbuttons (Up/Down)<br>2 Pushbuttons (Tilt adjustment) |

## ELECTRICAL

|                   |                                   |
|-------------------|-----------------------------------|
| Power Adaptor     | 90 ~ 264VAC to 12VDC<br>47 ~ 63Hz |
| Power Consumption | 30W                               |
| Energy Management | VESA DPMS                         |

## MECHANICAL (SFOL156G-10)

|                           |                 |
|---------------------------|-----------------|
| Screen (mm)               | 400 x 265       |
| On-table Cover Plate (mm) | 470 x 395       |
| Under-table Housing (mm)  | 524 x 398 x 106 |
| NET Weight (Kg)           | TBD             |
| Packaging dimensions (mm) | 600x720x190     |
| Gross Weight (Kg)         | TBD             |

## ENVIRONMENTAL CONDITIONS

|                        |             |
|------------------------|-------------|
| Operation Temperature  | 0° to 50°   |
| Storage Temperature    | -20° to 60° |
| Operation Humidity (%) | 20 to 80    |
| Storage Humidity (%)   | 10 to 90    |

## OTHERS

|                |                                 |
|----------------|---------------------------------|
| Certifications | CE, RoHS, BIS, EAC, CB IEC EE   |
| Plug & Play    | VESA DDC2Bi                     |
| Accessories    | Mains Power Cord<br>User Manual |

Specifications subject to change without prior notice

