

SARM270M-10

DATA SHEET

ARM M Line



ARM M Line · Rear Vesa Mount Monitors

Designed to be installed with any standard VESA bracket.



SARM270M-10

SOLTEC TECHNICAL SPECIFICATIONS

REAR VESA MOUNT MONITORS

ARM M Line

GENERAL DESCRIPTION

27.0" Professional TFT Monitor.

Designed to be installed with any standard VESA bracket.
All monitors are available as a basic monitor, with a built-in PC and with a built-in digital media player.

Full range of options available.



DISPLAY

Panel Technology	Edge LED Technology
Display Area (mm)	597.6 (H) x 336.15 (V)
Size	27"
Pixel Pitch (mm)	0.311 x 0.311
Screen Aspect	16:9
Native Resolution	1920 x 1080
Viewing Angle UDLR	89°/89°/89°/89°
Contrast Ratio	3000:1 (Typ)
Brightness cd/m2	350 (Typ)
Colors	16.7 M Colors
Response Time	12ms Ton + Toff
Life Time (hours)	50.000

CONNECTIVITY

Analogue RGB Input	1xDB15
Digital Input	1xDVI
Display Port	DP 1.1a
Plug & Play	VESA DDV2Bi
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

ELECTRICAL

Power Supply Input	110/220VAC 50-60Hz
LCD Consumption	30W
Energy Management	VESA DPMS

MECHANICAL (SARM270M-10)

VESA Mount	100x100 M4
Net (WxHxD)	660x407x75
Net Weight (Kg)	9
Packing	770x510x220

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	10 to 90
Storage Humidity (%)	10 to 90

OTHERS

Certifications	CE; RoHS
Accessories	Mains Power Cord User Manual

ORDERING INFORMATION

SARM270M-10	Standard 27.0" ARM-M Line
SARM270M-18	27.0" ARM-M Line with built-in PC Intel J3455 Quadcore CPU RAM 4GB DDR3 Intel HD Graphics Chipset
SARM270M-15	27.0" ARM-M Line with built-in DMP Digital Media Player

Specifications subject to change without prior notice

SARM270M-10

SOLTEC
STANDARD AVAILABLE OPTIONS

REAR VESA MOUNT MONITORS

ARM M Line

27.0" Professional TFT Monitor designed to be installed with any standard VESA bracket.

Full HD Panel



PC Integrated



Horizontal Orientation



Touch Screen



Protective glass



Vertical Orientation




High Brightness



RS-232



RS-485



ORDERING INFORMATION OPTIONS

CVBS-IN

Composite Video Input RCA

CVBS-INOUT

Composite Video Input / Output BNC

I3 - CPU

Intel i3 CPU upgrade

I5 - CPU

Intel i5 CPU upgrade

I7 - CPU

Intel i7 CPU upgrade

8RAM

8GB RAM DDR3 upgrade

16RAM

16GB RAM DDR3 upgrade

32RAM

32GB RAM DDR3 upgrade

PCT270IN

27.0" Projected Capacitive Touch Screen

IR270-2

27.0" Infrared Technology

270HB

1500cd/m² High Brightness TFT option

RS232

RS-232 Serial Control DB9 Connector

RS485

RS-485 Serial Control RJ45 Connector in/out

DMP

Built-in Digital Media Player

G270L

27.0" 6mm Laminated Protective Glass

G270AGL

27.0" 6mm Anti-Glare Laminated Protective Glass

CUSTOMIZED COLOR

RAL Palette



Specifications subject to change without prior notice

