

SARM650M-10

DATA SHEET

ARM M Line



ARM M Line · Rear Vesa Mount Monitors

Designed to be installed with any standard VESA bracket.



SARM650M-10

SOLTEC TECHNICAL SPECIFICATIONS

REAR VESA MOUNT MONITORS

ARM M Line

GENERAL DESCRIPTION

65.0" Professional TFT Monitor.

Designed to be installed with any standard VESA bracket.
All monitors are available as a basic monitor, with a built-in PC and with a built-in digital media player.

Full range of options available.



DISPLAY

Panel Technology	S-PVA Edge LED
Display Area (mm)	1428.48 (H) x 803.52 (V)
Size	65"
Pixel Pitch (mm)	0.372 x 0.372
Screen Aspect	16:9
Native Resolution	3.840 x 2.160
Viewing Angle UDLR	89°/89°/89°/89°
Contrast Ratio	4000:1 (Typ)
Brightness cd/m2	500 (Typ)
Colors	1.07 B Colors
Response Time	8ms Ton + Toff
Life Time (hours)	60.000

CONNECTIVITY

Digital Input	2xDVI
Display Port	2xDP 1.2
Plug & Play	VESA DDV2Bi
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

ELECTRICAL

Power Supply Input	110/220VAC 50-60Hz
LCD Consumption	190W
Energy Management	VESA DPMS

MECHANICAL (SARM650M-10)

VESA Mount	800x400
Net (WxHxD)	1555x925x90
Net Weight (Kg)	65
Packing	1650x1025x225

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	10 to 90
Storage Humidity (%)	10 to 90

OTHERS

Certifications	CE; RoHS
Accessories	Mains Power Cord User Manual

ORDERING INFORMATION

SARM650M-10	Standard 65.0" ARM-M Line
SARM650M-18	65.0" ARM-M Line with built-in PC Intel J3455 Quardcore CPU RAM 4GB DDR3 Intel HD Graphics Chipset
SARM650M-15	65.0" ARM-M Line with built-in DMP Digital Media Player

Specifications subject to change without prior notice

SARM650M-10

SOLTEC


STANDARD AVAILABLE OPTIONS

REAR VESA MOUNT MONITORS

ARM M Line

65.0" Professional TFT Monitor designed to be installed with any standard VESA bracket.

Built-in DMP



PC Integrated



Touch Screen




Vertical Orientation




Protective glass




Housing Customization




CVBS



RS-232



RS-485



ORDERING INFORMATION OPTIONS

CVBS-IN

Composite Video Input RCA

CVBS-INOUT

Composite Video Input / Output BNC

I3 - CPU

Intel i3 CPU upgrade

I5 - CPU

Intel i5 CPU upgrade

I7 - CPU

Intel i7 CPU upgrade

8RAM

8GB RAM DDR3 upgrade

16RAM

16GB RAM DDR3 upgrade

32RAM

32GB RAM DDR3 upgrade

PCT650IN

65.0" Projected Capacitive Touch Screen

IR650-2

65.0" Infrared Technology

RS232

RS-232 Serial Control DB9 Connector

RS485

RS-485 Serial Control RJ45 Connector in/out

DMP

Built-in Digital Media Player

G650L

65.0" 6mm Laminated Protective Glass

G650AGL

65.0" 6mm Anti-Glare Laminated Protective Glass

CUSTOMIZED COLOR

RAL Palette



Specifications subject to change without prior notice

SARM650M-10

SOLTEC
GENERAL DIMENSIONS


REAR VESA MOUNT MONITORS

ARM M Line

CONSULTANTS & ARCHITECTS

Technical product description

65.0" Professional 24/7 Monitors with rear VESA mount compatible with any standard VESA bracket on the market. Native resolution 3.840 x 2.160. 2x DVI and 2x Display Port inputs. It can be with a built-in Industrial Computer or a Digital Media Player.



Illustrated standard model without built-in PC



