

# ZINIA185ARM13

DATA SHEET

ZINIA ARM Line



## ZINIA ARM Line • Ultra-wide TFT Monitor

Ultra-wide Professional TFT Monitor design to be installed with any standard VESA bracket



# ZINIA185ARM13

ULTRA-WIDE TFT MONITOR

ZINIA ARM Line

### GENERAL DESCRIPTION

Ultra-wide Professional TFT Monitor designed to be installed with any standard VESA bracket. Available as a basic monitor, with a built-in PC and with a built-in digital media player.

High Brightness

Protective glass

PC Integrated

Full HD Panel

Full range of options available.



#### DISPLAY

|                    |                     |
|--------------------|---------------------|
| Panel Technology   | Edge LED Technology |
| Display Area (mm)  | 410 (H) x 77 (V)    |
| Size               | 1/3 of 18.5"        |
| Screen Aspect      | 16:3                |
| Native Resolution  | 1.366 x 256         |
| Viewing Angle UDLR | 160°/160°           |
| Contrast Ratio     | 1200:1 (Typ)        |
| Brightness cd/m2   | 300 (Typ)           |
| Colors             | 16.7 M Colors       |
| Life Time (hours)  | 50.000              |

#### CONNECTIVITY

|                    |                  |
|--------------------|------------------|
| VGA Input          | 1xDB15           |
| Digital Input      | 1xDVI            |
| Plug & Play        | VESA DDC2Bi      |
| Auto Detection     | Yes              |
| No Signal Detected | Standby Mode     |
| Identification     | DDC2Bi EDiD v1.3 |

#### ELECTRICAL

|                    |                    |
|--------------------|--------------------|
| Power Supply Input | 110/220VAC 50~60Hz |
| LCD Consumption    | 15W                |
| Energy Management  | VESA DPMS          |

#### MECHANICAL (ZINIA185ARM13)

|             |     |
|-------------|-----|
| VESA Mount  | TBD |
| Net (WxHxD) | TBD |
| Net Weight  | TBD |
| Packing     | TBD |

#### ENVIRONMENTAL CONDITIONS

|                        |             |
|------------------------|-------------|
| Operation Temperature  | 0° to 50°   |
| Storage Temperature    | -20° to 60° |
| Operation Humidity (%) | 10 to 90    |
| Storage Humidity (%)   | 10 to 90    |

#### OTHERS

|                |                                 |
|----------------|---------------------------------|
| Certifications | CE; RoHS                        |
| Accessories    | Mains Power Cord<br>User Manual |

#### OPTIONS

|                      |                                        |
|----------------------|----------------------------------------|
| Industrial Computer  | Intel QuadCore J4125<br>4GB RAM 120SSD |
| Digital Media Player | Full HD Built-in Player                |
| Protective Glass     | 4mm Tempered glass                     |

