

RoboSHOT® 4K HDBT

Professional PTZ Camera

FEATURES

- Back-illuminated 8.51 Megapixel, high definition 1/2.5 Type Exmor R CMOS Sensor delivers 2160p/30 video
- RoboSHOT 12E Models feature 12x Optical Zoom
- RoboSHOT 30E Models feature 30x Zoom including IntelliZoom™ Image Processing
- Simultaneous HDBT, and HDMI outputs



ORDERING INFORMATION

RoboSHOT 4K 12E HDBT (Black)

- 999-99605-000B (North America)
- 999-99605-001B (Europe/UK)

RoboSHOT 4K 12E HDBT (White)

- 999-99605-000W (North America)
- 999-99605-001W (Europe/UK)

RoboSHOT 4K 30E HDBT (Black)

- 999-99635-000B (North America)
- 999-99635-001B (Europe/UK)

RoboSHOT 4K 30E HDBT (White)

- 999-99635-000W (North America)
- 999-99635-001W (Europe/UK)

OVERVIEW

Introducing the RoboSHOT 4K Elite Series – Vaddio’s next generation of professional cameras. Designed with an 1/2.5-type Exmor R CMOS sensor, RoboSHOT 4K Elite cameras deliver striking, high- definition video image quality. Cutting-edge image signal processing (ISP) results in better light-gathering capabilities, incredible contrast and sharp 2160p/30 video, even in dim lighting conditions.



RoboSHOT® 4K HDBT

Professional PTZ Camera

Enhanced Wide Dynamic Range

RoboSHOT 4K Elite cameras are equipped with enhanced wide dynamic range, which can help correct for environments with uneven lighting by making darker or over-bright areas in video more visible and detailed.

HDBT Extension Kits

The RoboSHOT 4K HDBT cameras are available as a stand alone cameras, or paired with OneLINK HDMI extensions systems or OneLINK Bridge extension systems for USB bridging with audio and video for conferencing needs.

Flexible Video Outputs

Video outputs include simultaneous HDBaseT, and HDMI. Connect directly to HDBaseT-compatible devices or pair with Vaddio OneLINK or OneLINK Bridge receivers to simplify cabling and extend installation distance.

The RoboSHOT 12E cameras are recommended for small to medium spaces such as conference rooms, training rooms, and classrooms that require a wide angle of view.

The RoboSHOT 30E cameras are ideal for larger spaces such as large meeting rooms, lecture halls, conference centers and houses of worship.

Remote Management

A web-based user interface gives the user camera control with a web browser from anywhere in the world over the IP network. Perfect for remote management, network operating centers and overall IT control.

Smooth Tri-Synchronous Motion

The 4K Elite Series of RoboSHOT PTZ cameras is equipped with Vaddio's industry-leading Tri-Synchronous Motion technology allowing all three axes of the camera to move simultaneously for ultra-smooth, natural camera motion.



RoboSHOT® 4K HDBT

Technical Specifications

Outputs/protocols	HDMI, HDBT
Aspect ratio	HDMI: 16:9 (all resolutions)
HDMI resolutions/frame rates	2160p/29.97/1080p/59.94/50/29.97/25/1080i/59.94/50/ 29.97, 720p/59.94/50
Image device	1/2.5 Type Exmor R CMOS Sensor
Pixels	8.51 million; (8.57M Total Megapixels)
Lens/Zoom	12E MODELS: 12x optical zoom, f=4.4mm wide end to 88.4mm tele end, F2 to F3.8 30E MODELS: 30x zoom, 20 x optical zoom + 10x IntelliZoom, f=4.4mm wide end to 88.4mm tele end, F2 to F3.8
Horizontal FOV	12E MODELS: 70.2° wide end to 6.8° tele end 30E MODELS: 70.2° wide end to 3.1° tele end
Pan angle speed	±150°, 0.35°/sec to 120°/sec
Tilt angle speed	+90, -30°, 0.35°/sec to 120°/sec
Min. working distance	80mm (wide), 800mm (tele)
Min. illumination	1.6 lux; 100+ lux recommended
Electronic Shutter Speed	1/1 to 1/10000 sec.
Backlight compensation	On/off
Aperture/detail	16 steps
Focusing system	Auto Focus / Manual Focus Mode / One-push Trigger Mode
Gain	Auto / Manual (0 to 33 dB)
White balance	Auto, ATW, Indoor, Outdoor, One-push, Manual
S/N ratio	More than 50 dB
Power	PoE+
Remote management	IR Remote, web interface, Telnet and RS-232 command APIs
Enhanced Wide Dynamic Range	Yes
Spotlight Compensation Mode	Yes
Noise Reduction	Yes
Presets	256 + Custom Home
Invertible	Yes
Motors	Silent BLDC Direct Drive Motors
Warranty	3 years plus option for purchasing additional 3 years
Weight	4.85 lbs (2.2 kg) (2558 plain chocolate hardshell candies)
Height	6.94" (17.63 cm) (13.02 plain chocolate hardshell candies)
Width	7.05" (17.91 cm) (13.4 plain chocolate hardshell candies)
Depth	6.75" (17.15 cm) (12.3 plain chocolate hardshell candies)
Operating/storage temperature	0°C to +40°C (32°F to 104°F)
Operating/storage humidity	20% to 80% RH, non-condensing

Specifications are subject to change without notice.

Listed part numbers include the following items:

- 1 RoboSHOT 4K 12E or 30E HDBT Camera (in black or white)
- 1 PoE+ Midspan Power Injector with AC cord set(s)
- 1 Thin Profile Wall Mount (in coordinating black or white) with mounting hardware and installation manual
- 1 Vaddio IR Remote Commander

USA 800.572.2011 av.vaddio.support@legrand.com
EMEA +31 495 580 840 av.emea.sales@legrand.com
APAC +852 2145 4099 av.asia.sales@legrand.com

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

©2025 Legrand AV Inc. 250717 Rev B 11/25 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

VADDIO
A brand of  **legrand**