

USB-C® to HDMI® Dongle Adapter Converter **SKU: C2G30035**

This product has been discontinued. The replacement product is C2G54459.

This USB-C to HDMI Dongle Adapter Converter is an easy and convenient solution for connecting an HDMI monitor to a USB-C computer in your home or office. This adapter converter carries a digital video signal, supports up to a 4K resolution and meets the requirements of high performance applications.

Avoid frustration by simply plugging the adapter into your computer, then attach to the existing HDMI cable from your monitor or projector. The portable, compact design also makes it easy to carry in a laptop bag when traveling or on the go.

This adapter converter automatically converts the digital USB-C signal to HDMI, supporting full HD up to a 4K resolution at 60Hz.

Additional Technical Specifications

SIGNAL SPECIFICATIONS

- Testing: 100% Functional Test at 4K/60Hz/4:4:4 Resolution with Standard AV Test Equipment

ELECTRICAL SPECIFICATIONS

- USB-C to HDMI Adapter Power Consumption: 396mW (120mA/3.3V)

PHYSICAL SPECIFICATIONS

- Operating Temperature: 0°C - 40°C (0% - 90%RH)
- Storage Temperature: -10°C - 60°C (0% - 90%RH)

PHYSICAL CHARACTERISTICS

- HDMI 19pin Female Connector: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- USB Type-C Male Connector: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP Black, Shell: Nickel Plated
- Adapter Hood: Molded Black (Pantone/#Black 6C) PVC
- Color Band: Black (Pantone#Black 6C) 12 x 1.5mm
- 360° Solder to Connector Shell
- Product is CE Marked and Conforms to 2011/65/EU ROHS 2

Specifications

Dimensions &

Measurements

Cable Diameter	4.5 mm (0.2 in)
Cable Length	16.43 cm (6.5 in)
Operating Humidity Max	90% RH
Operating Humidity Min	0% RH
Operating Temperature	32° to 104°F (0° to 40°C)
Shipping Weight	0.02 kg (0.1 lbs)
Storage Humidity Max	90% RH
Storage Humidity Min	0% RH
Storage Temperature Max	60 Celsius (140 Fahrenheit)
Storage Temperature Min	-10 Celsius (14 Fahrenheit)

Characteristics & Features

Active/Passive	Active
Application	• Commercial • Residential
Color	Black
Connector 1	(1) USB-C Male
Connector 2	(1) HDMI Female
Product Type	• Active Device • Adapter • Converter
TAA Compliant	No
UPC	757120300359
Video Input Support	• HDMI • USB-C
Video Output Support	• HDMI • USB-C
Video Resolution	• 4K • 4K @ 60Hz

Certifications & Warranties

Certifications	• CE • FCC • NDAA 889 • Prop 65 • REACH • RoHS • TSCA
Data Transfer Rate	18 GBPS
Jacket Material	PVC
Warranty	5 years

