


Product: [BE46204](#) 



Life Cycle Status: Discontinued

4 PAIR AES/EBU, 26AWG, ISTP, FLEX, LSZH, STAGE

Product Description

4 PAIR AES/EBU, 26AWG/0.14mm², ISTP, FLEX, LSZH, STAGE

Technical Specifications

Product Overview

Suitable Applications:	Digital multi-modulation cable used in professional studios; For the transmission of analogue and digital audio signals; Designed to meet the requirements of the AES/EBU specification; The cable is very flexible and has a small outer diameter for use in applications where space is limited
------------------------	---

Product Life Cycle

Life Cycle:	Discontinued - the product is no longer manufactured
-------------	--

Construction Details

Conductor

Size	Stranding	Material
26	7x34	TC - Tinned Copper

Insulation

Material	Nom. Insulation Diameter	Color Code
PE - Polyethylene (Foam)	1.1 mm (0.043 in)	White & Blue

Inner Shield

Shield Type	Material
Spiral Serve / Screen	Tinned Copper (TC)

Outer Shield

Shield Type	Material
Braid	Tinned Copper (TC)

Inner Jacket

Material	Nom. Diameter
Nylon	2.8 mm (0.11 in)

Outer Jacket

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	9 mm (0.35 in)

Electrical Characteristics

Electricals

Max. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Characteristic Impedence	Nom. Velocity of Prop.
130 Ohm/km	50 pF/m (15 pF/ft)	110 Ohm	60%

High Frequency (Nominal/Typical)

Frequency	Nom. Insertion Loss (Attenuation) [dB/100m]
1 MHz	2.3
6 MHz	9.5

10 MHz	16
--------	----

Mechanical Characteristics

Bend Radius

Installation Min.
90 mm (3.5 in)

Standards and Compliance

Environmental Suitability:	Indoor
----------------------------	--------

History

Update and Revision:	Revision Number: 0.262 Revision Date: 03-18-2026
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
BE46204.01500	Black	Reel	500 m	8719605171894

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.