


LS550UCM-BF

55" FHD Video Wall Display Unit (Ultra Narrow Bezel 3.5mm)



Technical Specification

Model

Model	LS550UCM-BF
-------	-------------

System

Diagonal	55"(16:9)
LCD Technology	ADS
Resolution	1920×1080 (FHD)
Bezel width	2.3mm(U/L), 1.2mm(R/B)
Backlight	Direct LED
Brightness/Luminance	500 cd/m ²
Contrast Ratio	1200:1
Pixel Density	40dpi
Viewing Angle	H178°, V178°
Response time	8ms
Display Color	8bit(16.7M)
Color Temperature	10,000K
Surface Treatment	Haze 25%, 3H
MTBF	50,000h

Signals

Input	CVBS(BNC)×1, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1, USB×1, IR×1
Output	RS232×1

Features :

- Industrial level ADS LCD panel, suitable for continuous 24h/7 operation
- Ultra-narrow 3.5mm bezel-to bezel design(2.3mm bezel on the left and top sides and 1.2mm bezel on the right and bottom sides)
- Anti-glare, high contrast ratio and standard brightness greatly enhance the video layering, and present the details of the video
- High fidelity digital processing, brilliant and vivid video
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, USB
- Infrared, RS232 dual mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Fast stack installation, professional project design, supporting arc-shaped mounting
- Widely used in small-scale control room, commercial display etc.



General

Power Supply	AC100V ~ AC240V, 50/60 Hz	
Power Consumption (Standby)	≤0.5W	
Power Consumption (Typical)	95W	
Power Consumption (Max.)	166W	
Installation Mode	Floor-standing, wall-mounted	
VESA	600×400mm, M6	
Control Mode	Infrared, RS232 dual mode, supporting remote PC control	
Gross Weight	26.9kg(59.3lb) (One in one) 83.6kg(184.31lb) (Four in one)	
Net Weight	18.5kg(40.8lb)	
Dimension (W×H×D)	1213.7mm×684.5mm×85.9mm(47.8"×26.9"×3.4")	
Package (W×H×D)	1360mm×945mm×280mm(53.5"×37.2"×11.0") (One in one) 1360mm×885mm×567mm(53.6"×34.9"×22.3") (Four in one)	
Work Environment	Temperature	0℃~+50℃
	Humidity	10%RH~80%RH

Dimensions(mm)

