

# RT3MPR

3 pole male TINY xlr receptacle, rear mountable



## Article Variations

| Article Name | Details   | Packaging   |
|--------------|---|-------------|
| RT3MPR       | Nickel plated housing, gold plated contacts, max. panel thickness: 3 mm | Plastic Bag |
| RT3MPR-D     | Nickel plated housing, gold plated contacts, max. panel thickness: 3 mm | BULK        |

## Technical Information

| Product         |        |
|-----------------|--------|
| Title           | RT3MPR |
| Connection Type | XLR    |

| Electrical                |                           |
|---------------------------|---------------------------|
| Contact Resistance        | $\leq 10 \text{ m}\Omega$ |
| Insulation Resistance     | $> 1 \text{ G}\Omega$     |
| Dielectric Strength       | $> 500 \text{ V rms}$     |
| Rated current per contact | $< 5 \text{ A}$           |

| Mechanical |                                |
|------------|--------------------------------|
| Lifetime   | $> 1000 \text{ Mating Cycles}$ |
| Wiresize   | $0.22 \text{ mm}^2$            |
| Wiresize   | 24 AWG                         |

| <b>Material</b>     |                |
|---------------------|----------------|
| <b>Housing</b>      | Zinc           |
| <b>Nut</b>          | Brass          |
| <b>Washer</b>       | Steel          |
| <b>Plastic Body</b> | PA66+30%GF     |
| <b>Pin</b>          | Brass          |
| <b>Housing</b>      | Nickel Plating |
| <b>Nut</b>          | Nickel Plating |
| <b>Washer</b>       | Nickel Plating |
| <b>Pin</b>          | Gold Plating   |