



NSB2B-16/0

Type B, length 2, 16 IN (female/send)

Width: 117 mm, height: 79 mm, length: 252 mm

Supplied as disassembled set comprising of all hardware parts including plates, profiles, strain relief, end pieces and screws. Labels for channel numbering not included.

Technical Information

Product

| | |
|--------------|------------|
| Title | NSB2B-16/0 |
|--------------|------------|

Electrical

| | |
|----------------------------------|----------|
| Contact resistance | < 5 mΩ |
| Dielectric strength | 0.5 kVdc |
| Insulation resistance | ≥ 1 GΩ |
| Rated current per contact | 2 A |

Mechanical

| | |
|-------------------------|-------------------------------|
| Cable O.D. | 13 - 18 mm multicore |
| Insertion force | ≤ 10 N |
| Withdrawal force | ≥ 10 N |
| Lifetime | > 1000 mating cycles |
| Wiresize | 0.22 and 0.14 mm ² |
| Wiresize | 24 and 26 AWG |

Material

| | |
|--------------------|---------------|
| Shell | Aluminium |
| Quad plates | POM |
| End pieces | Thermoplastic |

Environmental

| | |
|--------------------------|------------------|
| Temperature range | -25 °C to +70 °C |
|--------------------------|------------------|

