

# NYS215

3 pole horizontal 1/4" jack, all contacts switched,  
chrome ferrule nut



## Article Variations

Article Name	Details	Packaging
NYS215	Stereo 3 pole, 8.2 mm distance to PCB	BULK
NYS2152	Mono 2 pole, 8.2 mm distance to PCB	BULK
NYS2152G	Mono 2 pole, gold contacts, 8.2 mm distance to PCB	BULK
NYS2152G-DI-U	Mono 2 pole, gold contacts, chrome ferrule nut, solder tap version	BULK

## Technical Information

### Product

<b>Title</b>	NYS215
<b>Connection Type</b>	Jack
<b>Gender</b>	female

### Electrical

<b>Dielectric strength</b>	0.5 kVdc
<b>Insulation resistance</b>	$\geq 1 \text{ G}\Omega$
<b>Rated current</b>	depends on mated connector
<b>Contact resistance</b>	depends on mated connector

### Mechanical

<b>Insertion force</b>	$\leq 20 \text{ N}$
<b>Withdrawal force</b>	$\geq 10 \text{ N}$
<b>Lifetime</b>	1000 mating cycles
<b>Wiresize</b>	

### Material

<b>Contact plating</b>	SnCe
<b>Contacts</b>	Brass (CuZn39Pb3)
<b>Shell / Insulation</b>	Thermoplastic

## Environmental

<b>Solderability</b>	Complies with IEC 68-2-20
<b>Temperature range</b>	-20 °C to +70 °C