



## NE8FAV-C5

Vertical PCB mount RJ45 receptacle, CAT5e, A-Series cutout with latch lock, max. panel thickness 3 mm

The etherCON Series is a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lightning network applications. The chassis connectors are shaped to fit into standardized panels out of the entertainment industry.

The all plastic A-Series offers the most space saving and cost effective design.

Attention! Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S\* cables.

## **Features & Benefits**

	odates rugged etherCON or any standard RJ45 plug	•	Approved latch lock system
<ul> <li>Most spa design</li> </ul>	ace saving and cost effective	•	Isolated to panel ground
front pan	PCB design at 24 mm distance to el – fits the widely accepted standard dimension for XLRs, s etc.	•	PoE+ compliant according to 802.3at Type2
•	erformance according to ISO/IEC nd TIA/EIA 568-C.2		



## **Technical Information**

Product		
Title	NE8FAV-C5	
Gender	female	

Electrical		
Contact resistance	< <b>50</b> mΩ	
Dielectric strength	1 kVdc	
Frequencyrange	1 - 100 MHz	
Insulation resistance	> 0.5 GΩ	
Rated current per contact	1.5 A	
Rated voltage	< 50 V	
Transmission performance	CAT5e, acc. TIA/EIA 586C.2, IEC11801	
Power over Ethernet	PoE+ acc. IEEE 802.3at	

## NEUTRIK

Mechanical		
Insertion force	≤ 20 N	
Withdrawal force	$\leq$ 20 N	
Lifetime	> 1000 mating cycles	
Panel thickness	max. 3 mm (0.12")	
Wiresize		
Wiring	Horizontal PCB mount	
Locking device	Latch lock	
Mounting direction	Rear mounting	
Chassis shape	Α	
Mounting	A-Screw	

Material	
Contact plating	0.2 μm Au over Ni plating
Contacts	Bronze (CuSn8)
Locking element	Ck 67 steel, treated
Shell	PBT D202G30

Environmental		
Flammability	UL 94 V-0	
Solderability	Complies with IEC 68-2-20	
Temperature range	-30 °C to +80 °C	