



NE8FAV-SD

Vertical PCB mount RJ45 receptacle, A-Series cutout with latch lock, with 2 additional screw domes for fixing the connector on the PCB (fixing screws included), max. panel thickness 3 mm.

The etherCON Series is a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lightning network applications. The chassis connectors are shaped to fit into standardized panels out of the entertainment industry.

The all plastic A-Series offers the most space saving and cost effective design.

Attention! Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S* cables.

Features & Benefits

Accommodates rugged etherCON NE8MC* or any standard RJ45 plug

Approved latch lock system

Most space saving and cost effective design

Complies with Class D according to TIA / EIA 568B and ISO / IEC 11801 standard

SD-Version with screw domes to fix connector onto PCB securely

Technical Information

Product	
Title	NE8FAV-SD
Gender	female

Electrical	
Contact resistance	< 50 mΩ
Dielectric strength	1 kVdc
Frequencyrange	1 - 100 MHz
Insulation resistance	> 0.5 GΩ
Rated current per contact	1,5 A
Rated voltage	< 50 V
Transmission performance	CAT5e
Standard compliance	TIA/EIA 586B, IEC11801

Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Panel thickness	max. 3 mm 0.12'
Wiresize	
Wiring	Vertical PCB mount with additional screw domes
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	A
Mounting	A-Screw

Material	
Contact plating	0.2 μm Au over Ni plating
Contacts	Bronze (CuSn8)
Insert	PBTP 15 % GR
Shell	PBTP 15 % GR

Environmental	
Flammability	UL 94 V-0
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C