

Overview

The HDMI 1x8 Splitter (500422) allows one (1) HDMI source to be distributed to up to eight (8) HDMI displays. The splitter supports up to 1080p, 12-bit Deep color and HD audio. The splitter is HDCP 1.3 compliant and features LED diagnostics. Additionally, all HDMI connectors are on the rear panel for neater cabling.

Applications
Commercial and residential AV systems
Classroom training systems
Digital signage
Boardroom systems
Medical video systems




Key Features

Distributes one HDMI source to eight displays Supports up to 1080p @ 60Hz, Deep Color 12-bit Supports 2K and 4K resolutions Supports Dolby TrueHD and DTS-HD Master Audio Connectors on rear panel for neater cabling Supports 3D LED diagnostics HDMI 1.4 HDCP 1.3 compliant

Specifications	
Environment	HDMI 1.4 (3D)
Devices	DVD/Blu-Ray, plasma, projecto rs, monitors, TV, PC, laptops
Transmission	Transparent to the user
Frequency	25 to 340 MHz
Signals	HDMI 1.4 protocol
Connectors	1 HDMI Type A Input
	8 HDMI Type A Output
LEDs	Power: Green
	Input & Output Link: Blue
Resolution	480i to 1080p @ 50/60 FPS
	1080p @ 24/50/60 FPS
	VGA to UXGA
Color	8, 10 & 12 bit
Audio	LPCM 7.1CH, Dolby TrueHD and DTS-HD Master Audio
HDCP	Revision 1.3
Cable	HDMI Cable
Temperature	Operating: 0° to 40°C Storage: -20° to 60°C
	Humidity: up to 90% non-condensing
Enclosure	Metal enclosure
Dimensions	10.63" x 4.33" x 1.18" (270 mm x 110 mm x 30 mm)
Weight	3.2 lbs (1.45 Kg)
Compliance	Regulatory: FCC, CE, RoHS
Warranty	2 years
Order Information	500422 HDMI 1x8 Splitter (UPC Code 627699004227)

© MuxLab Inc. 2014 HDMI 1x8 Splitter, 4K

Typical Applications





Rear panel

© MuxLab Inc. 2014 HDMI 1x8 Splitter, 4K

MuxLab Inc.
8495 Dalton Road, Mount Roya I, Quebec, Canada, H4T 1V5
Tel: (514) 905 0588 Fax: (514) 905 0589
Toll Free:1 877 689-5228
E-mail: videoease@muxlab.com
URL:www.muxlab.com