



High-Performance In-Wall Subwoofer

ISW-8 is Bowers & Wilkins flagship in-wall subwoofer; it delivers exceptional subwoofer performance for custom installed applications. It's a no-compromise design for when power and performance are key, but has a thin profile that allows it to fit into a 2in x 4in stud wall.

Advanced technology = high-performance sound

ISW-8 features the longest excursion from an in-wall subwoofer Bowers & Wilkins has ever made. Its 12in Aerofoil driver uses Neodymium magnets and can deliver both incredible levels of power and precise control for a sensational listening experience.



Reduced vibration

To counter the incredible power on offer, the ISW-8's backbox is designed to be hung from the wall using new Integrated vibration isolation mounts. This helps reduce any vibration transferring from the cabinet to the walls, providing both improved performance and structural integrity.

Designed to work with the best

ISW-8 is primarily targeted to work with Bowers & Wilkins high-end CI700 and CI800 custom installation speakers in both home cinema and high-performance two-channel installations.





ISW-8

Type In-wall Subwoofer

Drivers

Driver size: 12in
Cone material: Aerofoil™ Profile bass cone
Impedance: 8Ω
Power handling: 1000W
Frequency response (-3dB): 16Hz-200Hz
Frequency range (6dB): 12Hz-260Hz

Cabinet

Description: Closed-box subwoofer
Cabinet dimensions: Height: 1640mm (64.6in)
Width: 350mm (13.8in)
Depth: 84mm (3.3in)
Material: MDF
Bracing: Yes
Volume: 30L

Baffle

Baffle dimensions Height: 400mm (15.8in)
Width: 400mm (15.8in)
Depth: 8.5mm (0.3in)