


Datasheet for APPC-Series



PRO DVX | ALWAYS ON

ProDVX Europe B.V.

Europalaan 10
5232 BC, Den Bosch
The Netherlands

+31 (0)73 737 0345
sales@prodvx.com

Android Panel PCs

APPC-32X-R23 (7001)

Panel

Size	31.5"
Resolution	1920 x 1080
Brightness	350 cd/m2
Viewing Angle	H 178° / V 178°
Treatment	Anti-glare
Touch Type	10 point touch projected capacitive
Contrast Ratio	3000 : 1
Cover glass	>6H - 3.4mm
Haze	4~10%
Aspect Ratio	16:9 wide

Physical

Housing	Metal
Color	Black
Weight	10540 g
Dimensions	767,7 x 469,2 x 59 mm
Mounting / VESA	VESA 200
Power Supply	AC 110 V - 240 V
Power Supply included?	Yes
Power Usage	50 ~ 75 Watt

System

CPU	RK3399 (Dual Core Cortex A72 with Quad Core A53)
GPU	MALI T860MP4
System Memory	4GB LPDDR4 SDRAM
Internal Storage	16 GB eMMC Flash
OS	Android 11
Network LAN RJ45	10/100/1000 Mbps LAN
Power over Ethernet (PoE)	N/A
WiFi	802.11 a/b/g/n
Bluetooth	BT 5.2
Storage / Working Humidity	10 ~ 90 % non-condensing
Storage Temp	-10 ~ 55 degrees C
Working Temp	0 ~ 40 degrees C

Other

I/O Ports	mini HDMI out, 2x USB 2.0, GPIO, USB-C, USB 3.0, 3x Pogo pin, 240 V DC-IN, 2x RS232, 3.5 mm jack in/out, Ethernet (RJ45)
Microphone	N/A
Speakers	2 x 3 W
LED Light Bar	Optional accessory
Integrated NFC	Optional accessory
Camera	Optional accessory
Safety features	IEEE 802.1X PEAP/TLS/TTLS support on LAN and WiFi
Standard Warranty	3 years

