

PrimeSHOT 10 HDMI

HD PTZ Camera

ORDERING INFORMATION

Black

999-30410-000 (North America)

999-30410-001 (Europe/UK)

999-30410-009 (Australia/New Zealand)

White

999-30410-000W (North America)

999-30410-001W (Europe/UK)

999-30410-009W (Australia/New Zealand)

OVERVIEW

Vaddio's PrimeSHOT 10 HDMI camera offers high-definition performance at an outstanding value. Ideal for meeting rooms, lecture halls and houses of worship, PrimeSHOT 10 HDMI provides outstanding low-light performance, and excellent 1080p image quality.

With simultaneous HDMI and IP streaming outputs, the PrimeSHOT 10 can broadcast the stream directly to your preferred live streaming client and send video to a local display for easy IMAG (image magnification).

PrimeSHOT 10 HDMI features 10x optical zoom, plus an easy, intuitive web-based user interface for remote configuration, management and control. Customizable PTZ presets and controls make PrimeSHOT 10 perfect for rooms with multiple focus points.



FEATURES

- 10x zoom with 67 degree horizontal field of view
- Simultaneous HDMI and H.264 (RTSP or RTMP) IP streaming outputs
- Video image adjustments such as manual color compensation, saturation and iris
- Custom PTZ presets
- Free Vaddio Deployment Tool for remote management, updates and more



A brand of **legrand**

COMMERCIAL AV BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

Vaddio PrimeSHOT 10 HDMI

TECHNICAL SPECIFICATIONS

CAMERA & IMAGE	Outputs/protocols	HDMI 1.4b, H.264 (RTSP or RTMP) IP streaming
	Aspect ratio	16:9 and 4:3
	Resolutions/frame rates	FHD: 1080p/60/59.94/50/29.97/25,1080i/60/59.94/50 HD: 720p/60/59.94/50
	Image device	1/2.8-Type Exmor CMOS Sensor
	Pixels	2.14 million (effective)
	Lens and Horizontal FOV	10x zoom, 67° (Wide End) 3.1° (Tele End)
	Pan angle speed	± 165°, up to 90°/sec
	Tilt angle speed	+90° -30°, up to 90°/sec
	Min. working distance	10mm (wide), 1.0m (tele)
	Min. illumination	100+ lux recommended
	Backlight compensation	On/off
	Aperture/detail	16 steps
	Focusing system	Auto Focus / Manual Focus Mode
	Gain	Auto / Manual (0 to 33 dB)
	White balance	Auto, One-push, Manual
	S/N ratio	More than 50 dB
	Power	12 VDC, 1.5 A
	Remote management	Wireless IR remote, web interface via browser, Vaddio Deployment Tool or Vaddio Device Controller, Telnet and RS-232 command APIs
	Enhanced Wide Dynamic Range	Yes
	Spotlight Compensation Mode	Yes
Noise Reduction	Yes	
Presets	16 + Custom Home	
Invertible	Yes	
Motors	Silent Direct Drive Motors	
Warranty	3 years with 1 year Advanced Replacement	
PHYSICAL & ENVIRONMENTAL	Weight	3.0 lbs (1.36 kg)
	Height	6.3 in. (163 mm)
	Width	6.1 in. (155 mm)
	Depth	5.5 in. (145 mm)
	Operating/storage temperature	0°C to +40°C (32°F to 104°F)
	Operating/storage humidity (relative)	20% to 80% RH, non-condensing

Specifications are subject to change without notice

WHAT'S IN THE BOX:

- PrimeSHOT 10 HDMI Camera (black or white)
- Thin Profile Wall Mount and hardware (black or white) and installation manual
- Vaddio IR Remote Master
- 12V power supply with AC cord set(s)
- Quick-Start card

THE ART OF EASY | legrandav.com

USA 800.572.2011 avvaddio.support@legrand.com
 EMEA +31.495.580.840 av.emea.sales@legrand.com
 APAC +852.2145.4099 av.asia.sales@legrand.com

©2023 Legrand AV Inc. 230524 Rev A 7/23 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

A brand of  **legrand**

COMMERCIAL AV BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold