Overview:

The 8 Button IP PoE Control Panel is a versatile wall or table-top mounted control panel for MuxLab AV over IP devices, TCP/IP & Telnet devices, select Matrix Switches, and third party products. Each button is programmable. The unit supports one (1) Ethernet port (for TCP/IP and Telnet), two (2) RS232 ports, one (1) Infrared port, and two (2) Relay ports, for control of end devices. The 8 Button IP PoE Control Panel can control MuxLab products including MuxLab's AV over IP system via the 500811 ProDigital Network Controller, MuxLab's TCP/IP, Telnet and RS232 managed Matrix Switches, as well as third party devices such as projectors and projector screens, displays, AV sources and other similar devices. The 500816-IP is managed via a web interface to program each key and to support IR learning. Each button on the 500816-IP unit can be programmed to execute up to 6 commands, and can even execute commands programmed on another unit.

Applications:

- Commercial and residential AV systems
- Classroom AV systems
- Boardroom systems
- Home Theatre
- Showroom

Key Features:

- 8 button control panel
- Buttons can be individually programmed
- Control end devices via TCP/IP, Telnet, RS232, IR & Relay
- Programmable via Web Interface
- Buttons are backlit & support customizable labels
- May be wall or table top mounted
- Supports firmware updates via Web Interface
- Supports PoE

Specifications	
Devices	AV over IP Controller, Matrix Switch, DVD, projectors, monitors, TV.
Compatibility	Compatible with select MuxLab & third party products
Output Ports	One (1) Ethernet port for TCP/IP Two (2) RS232 ports One (1) Infrared Emitter port Two (2) Low voltage Relay ports
Control Port	One (1) Ethernet LAN Port (RJ45)
Connectors	One (1) RJ45 for TCP/IP & Telnet control, and for firmware upgrade Two (2) 3-pin terminal blocks (3.81 mm) for Serial (RS232) One (1) 2-pin terminal block (3.81 mm) for IR Two (2) 2-pin terminal blocks (3.81 mm) for Relay One (1) 2-pin terminal block (3.81 mm) for Power
Power Supply	One (1) 110-240VAC to 12VDC/1.0A power supply with US, UK & Euro Blade
Temperature	Operating: 0° to 40°C Storage: -20° to 70°C Humidity: Up to 95% non-condensing
Enclosure	Metal
Dimensions	4.49" x 2.76" x 1.41" (114mm x 70mm x 36mm)
Weight	0.75 lbs (0.34 kg)
Compliance	Regulatory: FCC, CE, RoHS
Warranty	2 years
Order Information	500816-IP 8 Button IP PoE Control Panel (UPC: 627699018163)

Typical Application

TCP/IP & Telnet	
RS232	
IR	
Relay	