


SDVoE-based Point-to-multipoint HDMI 2.0 over Fiber Optical Link Scaling Receiver

Optical HDMI 2.0 scaling receiver with analog audio output for point-to-multipoint (networked) application. Full 4K HDMI 2.0 and HDCP 2.3 compliant with scaling and seamless switching (SFP+ module not included)



Details

The **HDMI-OPTN-RX100A-SR** receiver devices are fiber extenders based on **SDVoE technology** and allow users to extend **HDMI 2.0 compliant** video, audio and control signals from a single source to multiple destinations through a **fiber optical** link.

Beyond the benefits of sending **high-resolution video** and **USB2.0 data** to a **distance of up to 10km via fiber**, the extenders are also able to handle various connectivity standards, including a 1G user Ethernet channel over the 10G link, as well as command injection into **RS-232**.

The in-built scaler can cater for adjusting the video content to the format of the attached display. Moreover, the scaler is also able to handle glitches in the video arriving at the input of the corresponding transmitter by outputting an uninterrupted HDMI signal.

The Gigabit Ethernet ports are also valuable additions, allowing users to connect Ethernet capable devices to the network directly through the OPTX extenders. This is particularly useful for controlling external devices like projectors and displays.

HDCP 2.3 and basic **EDID management** functionality are also among the features offered by these devices, such as their connectivity and easy integration into a wide range of AV operations and with 3rd party devices, such as the Christie Terra projector.



HDMI-OPTN-RX100A-SR

SKU: 91536001

Features

- **Transmission distance of up to 10km (when SM SFP+ module is used)**
- **Offers scaling for format conversion and uninterrupted output**
- **SFP+ cage for single mode or multimode SFP+ modules**
- **Allows for the transmission of HDMI 2.0, embedded audio, Ethernet, and RS-232 data between an extender pair through single mode or multimode fiber**
- **Supports HDMI 4K signal formats (4K UHD @60Hz RGB 4:4:4, up to 18 Gbps)**
- **HDR and Low Latency Dolby Vision support**
- **HDCP 2.3 compliant**
- **Compatible with third-party SDVoE devices and controllers**
- **Ethernet extension (1 Gbps)**
- **Command injection on RS-232**