

4K Streaming and Media Input Module for CALICO | PRO

C7-PRO-MEDIA



Overview

The 4K Streaming & Media input module for CALICO is a dual low latency H.264 & H.265 streaming decoder. It has IP source labeling and playback of video clips and stills from the on-board 128GB HDD.

Features

Combine streaming, file playback and still images for each video channel using playlists	Up to 20x playlists can be used per system
2 video channels 4K30 & HD or dual HD media playback	2160p (4096x2160) 30Hz
Decodes IP streams up to 4K	
IP Stream Labelling with on screen position adjustment	Separate, and in addition to CALICO labelling function
High resolution still image support	up to 4320p (7680x4320) stored, scaled to 2160p for playback
Hardware video engine handles smooth playback and scaling	
USB 3.0 port for file playback and content transfer to internal SSD	
128GB internal SSD storage for content	Video and still images
Two operational modes	2-channel 4K + 2K mode for file playback and streaming / 2-channel 4k + 4k synchronized playback mode (8x HD file playback)

Designed For

C7-PRO CALICO models with input expansion slots	Input expansion module for CALICO models only
---	---

Max Installable

C7-PRO-2200	2 module
-------------	----------

Installation

Field upgradable expansion module	Can be fitted in to slots 11 and 12
-----------------------------------	-------------------------------------

Caution*	This is not a hot-swappable item. To install or replace the unit has to be powered down and disconnected from the supply. Observe static safety precautions when handling the module. **
----------	--

Video Inputs	
RJ45 (VoIP - video over IP)	1x (up to 40 decoders can be stored in the system, and two simultaneous streams can be viewed live)
IP Processing	
Chroma sub-sampling	4:2:0 , 4:2:2
Video decoding	H.264 (Main, High), MPEG4, H.265/ HEVC (Main) 8-bit
Bit rates	Up to 50Mbit H264, 25Mbps H265 per stream (dual stream)
Unicast streams	RTSP, RTMP, HTTP, MPEG-TS
Multicast streams	RTSP, MPEG-TS
Media Handling	
External	1 x USB 3.0 Interface
Supported devices	Flash file systems FAT, FAT32, ext3, ext4, NTFS
Internal	High-speed storage 128GB
Remote	File transfer supported (FTP)
Maintenance / management	via CALICO studio
Supported Input Resolutions	
480i (720x480)	59.94Hz
480p (640x480)	60, 72, 75, 85Hz
480p (720x480)	59.94Hz
487i (720x487)	59.94Hz
576i (720x576)	50Hz
576p (720x576)	50Hz
600p (800x600)	56, 60, 72, 75, 85Hz
720p (1280x720)	29.97, 30, 50, 59.94, 60Hz
720p (1920x720)	60Hz
768p (1024x768)	60, 70, 75, 85Hz
768p (1280x768)	60, 75, 85Hz
768p (1360x768)	60Hz
800p (1280x800)	60, 75, 85Hz
864p (1152x864)	70, 75Hz
900p (1400x900)	60Hz
900p (1440x900)	60, 75, 85Hz
900p (1600x900)	60Hz
960p (1280x960)	60, 85Hz
980p (980x980)	75Hz
1024p (1280x1024)	50, 60, 75, 85Hz
1050p (1400x1050)	50, 60, 75Hz
1050p (1680x1050)	60Hz
1080i (1920x1080)	47.96, 48, 50, 59.94, 60Hz
1080p (1920x1080)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz
2160p (3840x2160)	23.98, 24, 25, 29.97, 30Hz
2160p (4096x2160)	23.98, 24, 25, 29.97, 30Hz

* This item is not hot-swappable

** Must be installed by a skilled professional

Media and Images	
Interfaces	USB 3.0, Internal Storage, Network
Video codecs	H.264 (CBP, Main, High), H.265/HEVC (Main)
Video formats	mp4, mov, mkv, m4v, ts, mts, m2ts, mt2, mpeg2
Playback bit rates (streaming and media playback)	H264 total data handling 100Mbps, single channel up to 50Mbps @4K30 (2nd render 1080p (1920x1080) 30Hz) H265 total data handling 50Mbps, single channel up to 25Mbps @4K30 (2nd render 1080p (1920x1080) 30Hz)
Still image	JPEG, PNG, BMP
File Playback Resolutions Supported	
Up to 2160p (3480x2160) 30Hz	Up to 1 (2nd render HD)
Up to 1080p (1920x1080) 60Hz	Up to 2
Up to 7680 x 4320 (8K) stored quality	Still Images / Playback at up to 2160p (4096x2160) 30Hz
Audio	
Supported sampling rate	44.1 / 48kHz
Sample size	24 bits
Supported channels	One stereo pair per input
Control Interface	
CALICO studio	
Warranty	
Limited warranty	5 years parts and labor**
Regulatory Compliance	
System / modules	FCC, CE, RoHS, UL, UKCA
Environmental	
Operating temperature	32° to 104°F (0° to +40°C)
Operating humidity	10% to 85%, Non-condensing
Storage temperature	14° to +158°F (-10° to +70°C)
Storage humidity	10% to 85%, Non-condensing
Power	
Powered by the CALICO main unit	