

DHI-LS-HW IR to RS232 Controller





Features :

 \cdot IR to RS232 signal for remote control in front of the video wall, easy and convenient

 \cdot One key turning the whole video wall on or off, or switching the signal source synchronously


 \cdot Compatible with Dahua all series LCD video walls, one device can control up to 16 display units

Technical Specification

Model		
Model	DHI-LS-HW	
General		
Signal Interface	IR(3.5mm)×1, RS232 in×1, RS232 out×1	
Accessory	IR cable×1, power adapter×1	
Power Supply	DC 12V	
Power Consumption	≤5W	
Net Weight	0.37kg(0.82lb)	
Gross Weight	0.42kg(0.93lb)	
Device Dimension (W×D×H)	126.4mm×69.3mm×31.0mm(5.0"×2.7"×1.2")	
Package Dimension (W×D×H)	170mm×166mm×65mm(6.7"×6.5"×2.6")	
Working Environment	Temperature	0°C~+50°C
	Humidity	10%RH~90%RH
Compatible LCD Video Wall	Dahua all series	

Dimensions(mm)





Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.