

Introduction

The Atlona LinkConnect™ AT-LC-UC2UC-2M USB-C to USB-C cable provides reliable, consistent AV performance, and comes with an Atlona Advantage lifetime warranty. The LinkConnect family of cables includes a comprehensive range of options for connector type, length, and budget, so it's easy to customize to fit any application.

Designed to work with the Pocket 3H (AT-PKT-3H) tabletop cable access enclosure and an Atlona switcher installed below the table, the LC-UC2UC-2M cable helps ensure a clean, uncluttered meeting space minimizing in-room cable issues.

Key Features

Installation made easy

- LinkConnect cables can be ordered with other Atlona equipment and arrive onsite together.
- Single source supplier minimizes installation delays and ensures compatibility.

Compatible with USB 3.1 Gen 1 specification

- Ideal for Atlona switchers with USB-C inputs for AV, data, and power.
- Supports device charging up to 60 watts @ 3 amps.

AT-LC-UC2UC Series 1



LinkConnect[™] **USB-C to USB-C Cable**2 meters

Specifications

Video			
Signal	Input - USB-C Output - USB-C		
Bandwidth	18 Gbps		
UHD/HD/SD	4096x2160@60/50/30/25/24Hz 3840×2160@60/50/30/25/24Hz 1920x1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1920x1080i@30/29.97/25Hz	720p@60/59.94/50Hz 576p@50Hz 576i@25Hz 480p@60/59.96Hz 480i@30Hz	
VESA All resolutions are 60Hz	2560×2048 2560×1600 2048×1536 1920×1200 1680×1050 1600×1200 1600×900 1440×900 1400×1050	1366×768 1360×768 1280×1024 1280×800 1280×768 1152×768 1024×768 800×600 640×480	
Color Space	YUV, RGB		
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0		
Color Depth	8-bit, 10-bit, 12-bit		
HDR	Up to 4K HDR10 @ 60 Hz, 4K Hybrid-Log Gamma (HLG) @ 60 Hz, and 4K Dolby [®] Vision™ @ 60 Hz		

Audio			
HDMI Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Cable		
Length	Feet	Meters
AT-LC-UC2UC-2	6.6	2
Shielding	Triple Shielded	
Diameter	Inches	Millimeters
AT-LC-UC2UC-2	0.29	7.3
Jacket Material	PVC	
Conductor AT-LC-UC2UC-2	30 AWG	
Connector	Gold-plated	
Screw	M2*0.4mm	
Bend Radius	100mm	
Fire Rating	CL2	

AT-LC-UC2UC Series 2



Copyright, Trademark, and Registration

© 2024 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see http://patents.dts.com. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).