SPECIFICATIONS

Interior dimensions	L15.0" × W10.5" × H6.2" L381mm x W267mm x H157mm
Exterior dimensions	L16.7" × W13.4" × H6.8" L424mm × W340mm × H173mm
Weight (empty)	5.1 lbs | 2.3 kg
Lid depth	2.1" | 53mm
Base depth	4.1" | 104mm
Max buoyancy	40 lbs | 18.1 kg
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	Yes
Watertight	Yes - IP67
Warranty	Conditional lifetime guarantee

CERTIFICATIONS

- IPX7 INGRESS PROTECTION - WATERPROOF
- IP6X INGRESS PROTECTION - DUSTPROOF
- ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
- 48cm(19") min. ASTM D-4169 DC-18 - DROP TEST
- ASTM D-4169 DC-18 - VIBRATION
- ASTM D-4169 DC-18 - RAINFALL
- 1 meter (3.28 ft) MIL-STD-810F - IMMERSION

MATERIALS

Case shell – NK-7 high impact polypropylene

Latches – Nylon 66

Handle – NK-7 high impact polypropylene | TPE

Purge valve – Nylon 66 | Gore® membrane | Silicone washers

Pins/hardware – 304 stainless steel

Gasket – EPDM

Copyright © 2019 Plasticase inc. All rights reserved.

NANUK™
PROFESSIONAL PROTECTIVE CASES

MEDIUM SERIES 920

STANDARD FEATURES

1 - Powerclaw latching system
2 - Waterproof IP67 rated
3 - Impact resistant NK-7 resin
4 - Padlockable
5 - Stackable
6 - Molded-in bezel system
7 - Soft grip handle stay
8 - Automatic pressure release valve
9 - Integrated lid stay
10 - 100% stainless steel hardware
11 - Lifetime guarantee

AVAILABLE COLORS

Black 0001

Graphite 0007

Olive 0006

Orange 0003

Silver 0005

Yellow 0004

AVAILABLE OPTIONS

Multilayer cubed foam

Padded divider

Aluminum panel kit

Lexan panel kit

TSA approved padlock

Shoulder strap

CUSTOM OPTIONS

Custom printing

Custom label

Custom foam

Custom panel

Copyright © 2019 Plasticase inc. All rights reserved.