

10.1" Mimo Myst Capture with HDMI Capture

MY-1090CP-G



Mimo Myst Capture with built in HDMI capture capability for the ultimate conference room solution.

10.1" Myst Capture with Capacitive Touch Display and HDMI Capture

This new generation display takes the best of the award-winning Mimo Vue Capture and levels it up by adding robust features that are sure to elevate any conference room space. With powerful new capabilities, a sleek and sophisticated high-end, low-profile design, plus a convenient USB connection, this feature-rich display is perfect for huddle rooms and other small conference rooms where space is at a premium and video conferencing is a priority.

An ideal 10.1" conference room interface at a truly accessible price point, the Mimo Myst Capture is fully compatible with all major conferencing software like Google Meet, Zoom Rooms, and Microsoft Teams for ultimate convenience and flexibility. With seamless setup and maximum visual appeal, this high bright, high contrast display has integrated HDMI capture, USB 2.0 pass thru for a speaker/mic box at the table, and is available with different mounts to accommodate the setup of your space. Additional features include integrated cable management and strain relief, two separate audio paths for speakers and headphones, multiple sensors including human presence for standby and low-power modes with auto wakeup.

The Mimo Myst Capture is truly built to support your conference room now and as the workplace evolves, allowing for the scaling of huddle rooms as well as accommodating for those working in the office and afar.

Features:

- 1280x800 USB connected touch display that is recognized by PCs as a regular display
- Compatible with Windows 8 (and higher), Linux, Chrome, and Mac OS*
- Integrated HDMI Capture up to 1080p in standard UVC and UAC protocol for wide software support
- USB input to optionally connect USB accessories such as a speaker/mic
- Externally powered via supplied AC/DC adapter or other 12V/2A source

Applications:

- Conference rooms
- Control interface where HDMI capture is needed



* With purchase of Mac touchscreen driver

Product Specifications

DISPLAY SECTION (Typical)	Video	USB	
	Resolution	1280 x 800	
	Size	10.1"	
	Touch	USB (HID Compliant)	PCAP
	Contrast	1000:1	
	Brightness	400	cd/m2
	Viewing Angle	85/85/85/85	U/D/L/R
MYST CAPTURE	Plug and Play	Yes	
	UP / Down Scaling	Yes	
	Firmware Upgradeable	Yes	
	Operating Temperature	-10 to 40	C
	Storage Temp	-30 to 60	C
	Power Consumption	12	W (max w/o USB accessory)
	Connections	USB to PC, HDMI capture, USB through	
	External Power	Supplied AC/DC adapter or other 12V/2A source	
	Measurements & Weight	8.375" x 10.25" x 5.5"	4.12lbs
	Human Presence Sensor	IR. 3m at +/- 90 degrees	
	Other Sensors	- Ambient Light - Orientation - Temperature (2x)	HID Sensor Compliant
	Stereo Audio	200 Hz-20 kHz, 1W max	
	Headset	Stereo with mic and jack detect	
	Mounting	Wall mountable with custom bracket	
	Cable channels	For strain relief with locking plate	
Security Slot	Kensington lock port		
Color	Gray		
Capture	USB Video Class	UVC	
	USB Audio Class	UAC	
	Resolution	up to 1080p	
Certifications	UL, FCC, CE, RoHS, RCM		



Mimo Monitors

743 Alexander Rd. Suite 15
Princeton, NJ 08540

info@mimomonitors.com

Sales: **1-855-YES-MIMO (937-6466)**

2021-0623
Rev 2 - 80914