



# AVer CAM130

# Brighter and Better Meetings 4K Camera with Intelligent Lighting for Small Rooms and WFH













#### **Camera**

**3** 4K optical lens, 120° FOV, up to 5X zoom via ePTZ\*

©Sony 4K sensor: ultra-crystal-clear image in any lighting

© Frame rates: (16:9) 4K 30fps; 1920 x 1080, 1600 x 900, 1280 x 720, 960 x 540, 848 x 480, 800 x 448, 640 x 360, at 60, 30, 15fps; (4:3) 1280 x 960, 800 x 600, 640 x 480 at 60, 30, 15fps

- ①Intelligent fill light: automatically adjusts lighting levels to make you look energetic in a dim environment\*\*
- Supports autofocus: SmartFrame function automatically adjusts
   the FOV to track and fit all participants on screen
- ①Innovative Preset Framing: follows the presenter through preset areas
- True WDR up to 120db: 3D noise-reduction and superb backlight compensation optimize lighting in high-contrast conditions
- Mirror, flip, AE, white balance: auto/manual override via PTZApp 2Minimum focus distance: 60 cm
- People-counting API: enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
- ©10 camera presets (through remote control and IP web page) ©Standard tripod screw holes
- \*Please use PTZApp 2 to set up 5X zoom.
- \*\*For best lighting results, sit within 1 meter away from the camera.

## Microphone

①2 omnidirectional microphones

®Frequency response: 100-12K Hz

\*\*Sensitivity: -37 dB

DEcho cancellation and background noise suppression

#### **Connectivity**

USB type-C 3.1 connector, backward compatible with USB 2.0
 DC jack for power adapter (for USB 2.0 connection while using fill-light function)

#### **Video Format**

YUV, YUY2, MJPEGH.264 (UVC 1.5)

#### **USB**

3.1 Gen 1, backward compatible with USB 2.0UVC 1.1 (USB video), UAC 1.0 (USB audio), UVC1.5\*

\*UVC1.5 requires an additional firmware upgrade. Please contact technical support for more details

# **Control**

IR remote controlUVC/UVA plug-and-playPTZApp 2

# **Security and Mount**

Built-in TV clipKensington slot1/4" tripod mounting screw

# **System Requirements**

Windows 7/10/11
 Mac OS X 14.4 or later
 Google Chromebox 3 version 94.0.4606.114 or later

#### **Hardware Specs**

⊕3.2 GHz Intel® Core™ i5-4460 processor
⊕4 GB RAM or more
⊕USB 3.1 port, backward compatible with USB 2.0

# **Power Supply**

**3** AC 100V–240V, 50/60 Hz **5** V/2A

# **Free Applications for Meeting Collaboration**

(For Windows® and Mac® computers)

#### EZManager 2: Camera Central Management Software

• Remotely group FW/SW upgrades, control the camera, and manage settings

# PTZApp 2: Camera Settings Software

- View live video, people-counting numbers, and meeting-interval information
- **©** Enable Skype for Business far-end control
- \*\*DUpgrade firmware automatically or manually
- **®**Control the camera
- Set parameters and adjust the camera image
- Diagnose operating status

#### EZLive: Broadcasting Software

①Enjoy multi-camera real-time streaming, annotating, image capturing, and video recording

#### **Environmental Data**

Department of to 40°C

Operation humidity: 20% to 80%

⊕Storage temperature: -20 to 60°C

**®**Storage humidity: 20% to 80%

#### **Dimensions**

Package dimensions: 217(L)\*155(W)\*118(H) mm

Package weight: 0.729 kg

@Camera: 160 (L) x 37 (H) x 60 (D) mm/ 0.282kg

®Remote control: 149.72 x 42.3 x 19.29 mm/50g (optional item)

# **Package Contents**

**©CAM130** unit

Power adapter (10 ft/3 m)

**OUSB 3.1 type-C to type-A cable (6 ft/1.8 m)** 

**OQR** code card

Tripod screw

### **Optional Accessories**

Remote control (also compatible with VB130) USB 2.0 type-C to type-A cable (15 ft/5 m)

\*USB 3.1 Extension Cable (10 m/20 m/30 m)

# **Warranty**

\*\*Camera: 3 years

① Accessories: 1 year

\*We offer an optional 2-year extended warranty in Europe. Please contact your local supplier for details.

# **Compatible Applications**

Zoom, Microsoft® Teams, Skype, Skype for Business, Google Meet, RingCentral, BlueJeans , Intel® Unite™, Fuze, Adobe® Connect™, CyberLink U Meeting®, Cisco WebEx® GoToMeeting™, LiveOn, Microsoft® Lync™, TrueConf, V-Cube, Vidyo, vMix, WebRTC, Wirecast, XSplit

\*For 4K UHD support, please check system/hardware requirements with your software application provider.

\*\*Specifications may vary depending on countries and are subject to change without notice.

# **Product Overview**





