

# Philips Signage Solutions 37BDL3050S/00 Signage Display 94 cm (37") 700 cd/m<sup>2</sup> Full HD Black Built-in processor Android 8.0 24/7

37IN Stetched Display 1920 x 540



<b>Brand</b>	Philips
<b>Product Code</b>	37BDL3050S/00
<b>Product URL</b>	<a href="https://www.lasystems.be/en/philips-37bdl3050s00">https://www.lasystems.be/en/philips-37bdl3050s00</a>



## General marketing text

Philips Signage Solutions 37BDL3050S/00 Signage Display 94 cm (37") 700 cd/m<sup>2</sup> Full HD Black Built-in processor Android 8.0 24/7

## Technical Specifications

### Display

Display diagonal	94 cm (37")
Display resolution	1920 x 540 pixels
Display brightness	700 cd/m <sup>2</sup>
HD type	Full HD
Native aspect ratio	32:9
Response time	8 ms
Contrast ratio (typical)	4000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.47 x 0.47 mm

### Ports & interfaces

HDMI ports quantity	2
USB port	✓
Ethernet LAN	✓
HDMI version	2.0
HDMI input ports quantity	1
HDMI output ports quantity	1
VGA (D-Sub) input ports	1
USB ports quantity	1
USB version	2.0
USB connector type	USB Type-A

## Ports & interfaces

Ethernet LAN (RJ-45) ports	1
PC Audio in	✓
RS-232 interface	✓
Remote (IR) input	1
Remote (IR) output	1

## Design

Product colour	Black
Placement supported	Indoor
VESA mounting	✓
Orientation	Horizontal
Panel mounting interface	400 x 200 mm

## Performance

On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Operating hours (hours/days)	24/7
Mean time between failures (MTBF)	50000 h

## Power

Power consumption (typical)	70 W
Power consumption (standby)	0.5 W
Input voltage	100/240 V
AC input voltage	100/240 V
AC input frequency	50/60 Hz

## Computer system

Built-in processor	✓
Internal memory	2 GB
On-board graphics card model	ARM Mali-G51
Internal storage capacity	8 GB
Operating system installed	Android 8.0

## Weight & dimensions

Display height	282.3 mm
Width	928.5 mm
Depth	48.7 mm
Height	282.3 mm
Weight	7.76 kg

## Packaging content

Remote control included	✓
Batteries included	✓
Cables included	AC, HDMI, IR sensor, RS-232
Mounting kit	✓

## Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 95%

## Certificates

Certification	THIS FCC Class A CB
---------------	---------------------

LASystems is not responsible for the errors in the documentation of products.

Pictures and description of Philips 37BDL3050S/00 are for your convenience only and may not be accurate. We will ship you the item based on the product name and manufacturer number only. For more technical information please visit the manufacturer's website.