



## X-24E

A durable, full-featured 24" FHD display specially designed for various professional and public environments, with new gamma and black level settings for the ideal images no matter the signal quality.

The X-24E's slate of features includes newly designed adjustable gamma curve, black level, and video mode settings which help fine-tune the display's visuals to ideal levels. Also newly added is a DisplayPort 1.2 input for speedy transmission of high-resolution video. Anti-Burn-in™ technology is included with the display, which prevents image burn-in on displays that work full-time. Overall the X-24E is engineered for a lifetime of use with rigorous screening of components, a durable metal exterior and a protective NeoV™ Optical Glass for greater protection.

- > LED-backlit technology with high FHD 1920 x 1080 resolution
- > Crisp 2,000,000 dynamic contrast ratio
- > Slim 14 mm border & bezel design for a stylish look
- > NeoV™ Optical Glass
- > AIP technology: PIP and PBP functions; 3D Comb Filter/Deinterlace/Noise Reduction
- > Selectable aspect ratio for ultimate image
- > EcoSmart Sensor for low watt power consumption
- > Black-level alignment
- > Versatile inputs: VGA, DVI, HDMI, DisplayPort, Audio in
- > Built-in speakers
- > Touch sensor control keys to prevent vandalism
- > Durable metal housing
- > Rigorous screening of the components for mission-critical 24/7 applications
- > Kensington® Security socket



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays



# X-24E

## Specifications

## X-24E

<b>Panel</b>	Panel Type	LED-backlit TFT LCD
	Panel Size	23.6"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.2715 mm
	Brightness	300 cd/m <sup>2</sup>
	Contrast Ratio	2,000,000 : 1 (DCR)
	Viewing Angle (H/V)	170°/160°
	Display Colour Response Time	16.7M 3 ms
<b>Frequency (H/V)</b>	H.Freq	24 kHz - 82 kHz
	V.Freq	50 Hz - 75 Hz
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	HDMI	HDMI
	DisplayPort	DisplayPort
<b>Audio</b>	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø)
	Speaker	2W x 2
<b>Power</b>	Power Supply	External
	Power Requirements	DC 12V
	Consumption	<19W (On) <0.3W (Stand-by) <0.3W (Off)
<b>NeoV™ Optical Glass</b>	Thickness	3.0 mm (0.12")
	Reflection Rate	< 1.8%
	Transmission Rate	≥ 97%
	Coating Hardness	> 9H
<b>Operating Conditions</b>	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10%~90% (No condensation)
<b>Storage Conditions</b>	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	5%~95% (No condensation)
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100mm & 75 x 75mm)
<b>Dimensions</b>	Product (W x H x D)	562 x 397 x 155 mm (22.1" x 15.6" x 6.1")
	Packaging (W x H x D)	676 x 525 x 213 mm (26.6" x 20.7" x 8.4")
<b>Weight (net)</b>	w/o base	7.2 kg (15.9 lbs)
	w base	7.8 kg (17.2 lbs)
	Packaging Weight	10.6 kg (23.4 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CE, RoHS, WEEE, REACH, GOST-R
<b>Accessories</b>	Supplied	CD ROM(user manual), power cord, power adapter, 15-Pin D-Sub cable, audio cable



Available in black or white



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



PIP, PBP and image enhancer



Multiple video inputs (HDMI, DVI, VGA, DisplayPort) make possible effortless system integration

Light environment  
(Brightness increased)



Dark environment  
(Brightness reduced)



EcoSmart Sensor and versatile capabilities ensure round-the-clock operations