

UBEX-PRO20-HDMI-F100 SKU: 9182000X

Optical AV Over IP Video System for 10G Networks

UBEX is an optical scaling extender which allows 4K UHD@60Hz 4:4:4 uncompressed signal extension with latency-free multistreaming. The device is designed to use Video Over IP transmission on a 10G Ethernet network.



Details

UBEX is an optical scaling extender which allows **4K UHD@60Hz 4:4:4 uncompressed signal extension with latency-free multistreaming**. The device is designed to use **Video Over IP transmission on a 10G Ethernet network**, it has standard, 10 Gbps **SFP+ optical modules** installed, which are field-exchangeable by the user.

UBEX units can connect to create a **complex network with the use of a standard Ethernet switch**.

An UBEX-MMU-X200 **Matrix Management Unit (MMU)** is required to **control and supervise a virtual matrix**, which can be created by connecting UBEX units as input and output endpoints to an Ethernet switch acting as crosspoint. The MMU device can **update the firmware of endpoint UBEX units** in a virtual matrix application **simultaneously**, without limitation for the number of devices in the setup.

One of the prime advantages of such new architecture is **scalability**: the virtual matrix created can have a **virtually infinite number of endpoints**, limited only by the number of open ports on the Ethernet switch used. Such a virtual matrix can be also extremely asymmetrical, as e.g. it could have only a few (or one) devices on the input side, while an almost unlimited number of output end units.

Using **visually lossless compression**, UBEX can **extend two Full 4K UHD signals over a single, 10 Gbps Ethernet port**. This generates **substantial cost saving** on the required Ethernet switch side, as with UBEX only half the router size is required compared to the needs of similar, 10 Gbps IP based architectures. For video signals which can be transferred within the 10G speed limit of a single optical fiber, a **video signal redundancy** feature is available employing the second optical fiber channel.

The UBEX design also favors **dual-screen applications**: each transmitter and each receiver handles 2x HDMI 2.0 video ports.

UBEX can also be used in a **point to point setup as a conventional extender** pair between endpoints. It is not required to use an Ethernet switch when point to point extension is required.

The **Video Wall Wizard** for UBEX features quick video wall installation with **bezel adjustment and cropping**, includes options for various layouts within the video wall matrix and also allows **zones for smart management**.

The maximum reachable **distance is ranging between 400 m and 80km**, depending on the type of singlemode or multimode optical modules installed in the device, and on the signal properties.

The internal **power source of UBEX has Medical (60601) and ITE (60950) grade classifications** for maximum reliability.

EUROTEMPEST

The UBEX-Pro20-HDMI-F100 successfully passed and got certified for the **Tempest SDIP27 Level B standard**, making it suitable for defense and intelligence projects where high levels of reliability is critical. Please find the certification document under our 'File Downloads' tab.



UBEX-PRO20-HDMI-F100 SKU: 9182000X



Front view



Rear view

Features

- **Scaling of video signals to match the properties of the target display/sink**
- **Support for high bitrate audio, including Dolby TrueHD, Dolby ATMOS and DTS-HD Master Audio**
- **HDR support**
- **4096x2160@60Hz/4:4:4 maximum resolution (600 MHz)**
- **Uncompressed video up to 18 Gbps datarate (600 MHz pixel clock)**
- Metal enclosure
- Supports all VESA and HDTV resolutions
- Advanced EDID Management
- Fully non-blocking switching architecture
- Supports HDMI 4K signal formats (4K UHD @60Hz RGB 4:4:4, up to 18 Gbps)
- HDCP 2.2 and HDCP 1.4 compliant with cross conversion capabilities
- HDMI 2.0, HDMI 1.4 and DVI 1.0 compliant
- Color subsampling option on outputs (4:4:4 to 4:2:0 downconversion)
- Pixel Accurate Reclocking
- Automatic or adjustable video format conversion (DVI, HDMI or HDMI deep color)
- Front to back cooling airflow
- Automatic or adjustable color space and color range conversion
- Status LED for extension link detection
- Built-in universal power supply
- Mounting options for rack, furniture or truss

Specifications

Part Number	Product Name	SFP+ Module Installed
91820001	UBEX-Pro20-HDMI-F100 RED	none
91820003	UBEX-Pro20-HDMI-F100 RED 2MM	2x 10G SFP+ multimode
91820002	UBEX-Pro20-HDMI-F100 RED 2SM	2x 10G SFP+ singlemode
91820010	UBEX-Pro20-HDMI-F100 RED 2xCAT	2x 10G SFP+ to RJ45

For further information on our SFP+ modules and color options please contact your regional Lightware Office or Lightware HQ.



UBEX-PRO20-HDMI-F100

SKU: 9182000X

Specifications

Hardware Features	UBEX-PRO20-HDMI-F100	UBEX-PRO20-HDMI-F110	UBEX-PRO20-HDMI-F120
Link	20G	20G	20G
Optical	✓	✓	✓
Type of videos	HDMI 2.0	HDMI 2.0	HDMI 2.0
Nr. of video inputs	2	2	2
Nr. of video outputs	2	2	2
USB HID (KVM)	✗	✗	✓
Balanced stereo analog audio I/O ports	✗	✓	✓
IR I/O and RS.232 control ports	✗	✓	✓
1 Gbps Ethernet	✓	✓	✓
Nr. of fibers (W/STANDARD SFP +)	4	4	4
Nr. of fibers (W/BIDI SFP +)	2	2	2

Software Features	UBEX-PRO20-HDMI-F100	UBEX-PRO20-HDMI-F110	UBEX-PRO20-HDMI-F120
4K scaling	✓ ¹	✓ ¹	✓ ¹
Framerate conversion	✓	✓	✓
4K UHD @ 60Hz 4:4:4	✓	✓	✓
30 bit deep color support	✓	✓	✓
Audio embedding and de-embedding	✗	✓	✓
Advanced edid management	✓	✓	✓
HDCP 2.2 compliant	✓	✓	✓
Seamless switching	✓	✓	✓

¹ : for only one video stream

