

VIDEO CONFERENCE SOLUTIONS

Let's

Communicate...

...with an Audipack video conference solution. Audipack video conferencing solutions are a great addition to your boardroom.



The video conference furniture

VCF-SL series: A slim and solid furniture available for 1 or 2 screens and 1 camera. Equipment is easy installed behind the removable rear panel, internal cables can be neatly organized.

Included:

Camera mount



Equipment mount Codec mount



Optional: Soundbar mounting brackets, (below screen installation)

19" codec mounting set

Passive Audipack sound bar (in cabinet installation)







The video conference floor stands

These versions are based on the standard 700 and 900 series floor stands (700 series page 16 and 900 series page 28).

Besides the fixed models, there are quick release models available that are ideal for rental purposes.

The video conference camera lift systems or drawers

Perfect solutions for installing and hiding cameras in furniture or a wall. With a push of a button the camera silently reveals itself.

- Suitable for any brand flat panel, camera and codec
- Modern and timeless design
- Generous access by removable rear panel to all the equipment (VCF-SL)
- Custom solutions available on request



Many practical accessories included (VCF-SL)



Very stylish designed (VCF-SL)



Very stylish designed (VCF-SL)



Generous access by removable rear panel

VIDEO CONFERENCE SOLUTIONS

75

(larger screens possible)

VIDEO CONFERENCE FURNITURE



Ref.	VCF-SL:

Dimensions in mm $W 970 \times D 600 \times H 1647$ Suitable for 1 screen

Presentation height (centre screen) Min. 1282 mm - Max. 1476 mm

Mounting interface VESA 300 x 300, 400 x 200, 400 x 400,

600 x 200, 600 x 400 and L&S 5

Inside cabinet dimensions in mm W 584 x D 200

Included VCF-SL-CP, Camera mount

VCF-SL-CM, Codec mount

VCF-SL-UMP, Universal equipment mount

Optional VCF-SL-3U, 19 inch, 3U equipment mount



Ref. VCF-SL2-55

Dimensions in mm W 2070 x D 600 x H 1647
Suitable for 2 screens (max. screen width 1270 mm)
Presentation height (centre screen) Min. 1252 mm - Max. 1538 mm







Dimensions in mm W 2310 x D 600 x H 1647
Suitable for 2 screens (max. screen width 1450 mm)
Presentation height (centre screen) Min. 1252 mm - Max. 1538 mm







Dimensions in mm W 2515 x D 600 x H 1647
Suitable for 2 screens (max. screen width 1700 mm)
Presentation height (centre screen) Min. 1252 mm - Max. 1538 mm

Max. mounting range in mm W x x H 446
Inside cabinet dimensions in mm W 584 x D 200



60









Ref. P5110

Max. camera dimensions in mm W 190 x D 250 x H 220 Stroke in mm 320 Round camera's

Optional wall switch & IR/RF remote
Power supply 110-230 VAC 50-60 Hz/24 VDC

Contact relay

Custom models available on request

Connectivity





Camera lift systems



110-230 VAC 50-60 Hz/24 VDC

Ref.	P5414
Dimensions in mm	W 400 x D 200 x H 751-1426

Max. camera dimensions in mm W 245 x D 180 x H 155
Stroke in mm 675
Connectivity Contact relay





Ref. P5466

Optional wall switch & IR/RF remote

 Dimensions in mm
 W 360 x D 245 x H 778-1453

 Max. camera dimensions in mm
 W 296 x D 180 x H 181

 Stroke in mm
 675

Contact relay





VIDEO CONFERENCE SOLUTIONS

ACCESSORIES

$oldsymbol{I}$ NTERNAL SOUNDBAR SYSTEM



Optional for video conference furniture VCF-SL1 & VCF-SL2



Ref.Description
Max. power

LSS-SB20 mono internal soundbar 1 x 30 Watt RMS stereo internal soundbar 2 x 20 Watt RMS

MOUNTING PLATE FOR VCF-SL1, LARGE & HEAVY SCREENS >60 KG









632342

UFPRO mount

Brand related mount

MOUNTING CAMS FOR DIRECT VESA MOUNTING



Ref.

392318 M8x13

390618 M10x13

For recessed mounting holes




392621 M6x35 **392620** M8x35

MOUNTING EQUIPMENT FOR VCF-SL1, VCF-SL2, VCF-SL2 -XL









VCF-SL-3U 19 inch/3U mounting set



VCF-SL-UMP
Mounting plate for additional

CAMERA WALL MOUNT



Ref. P6447