Liftomatic®

rental systems

The revolutionary flat panel Liftomatic®,

an all in one solution. The system lifts the flat panel out of a flightcase to the correct presentation height.

There is no better solution!



Stand above the crowd with

the Audipack **Liftomatic**®



Protect your equipment by using the Audipack Liftomatic flat panel lifting range.

The flat panel Liftomatic® is an all in one transport and presentation solution for screens up to 90"

Audipack offers two types of Liftomatic® systems;

Flightcase Liftomatic® systems. This flightcase with built-in telescopic lift system accommodates flat panels with a diagonal up to 65 inch. With just the push of a button your screen rises to a presentation height of 1800 mm (centre screen). Inside the flightcase is a big accessory compartment. As option there is a cover plate to cover the top of the flightcase in open position during use.

Liftomatic® systems with retractable wheel

Audipack also engineers and manufactures custom rental systems for the easy transportation and set up of LED and OLED walls. The high tech components and intuitive controls minimise the need for tools or the handling of products.

- One man floor operation
- ▲ Invisible lift mechanism
- ▲ Electrical or manual retractable wheels
- ▲ Available in various presentation heights

Flightcase Liftomatic®



All in one transport and presentation solution

Flightcase Liftomatic®



Available with optional cover plate

LIFTOMATIC® RENTAL SYSTEMS

Universal Flightcase Liftomatic® systems, a perfect rental system

Power supply: **230 VAC 50-60 Hz Including remote control**

Ref.
Flightcase dimensions in mm
Max. flat panel dimensions in mm
Presentation height (centre screen)
Mounting interface

FLM-4042 custom, depends on screen size W 980 x H 650

W 980 x H 65 1735 mm L&S 5

FLM-4650







Flightcase dimensions in mm Max. flat panel dimensions in mm Presentation height (centre screen) Mounting interface

custom, depends on screen size W 1160 x H 700

1735 mm L&S 5







Flightcase dimensions in mm Max. flat panel dimensions in mm Presentation height (centre screen) Mounting interface **FLM-5055** custom, depends on screen size

W 1350 x H 900 1735 mm L&S 5







Flightcase dimensions in mm Max. flat panel dimensions in mm Presentation height (centre screen) Mounting interface FLM-6065

custom, depends on screen size
W 1725 x H 960
1735 mm
L&S 5







For screen installation, an Audipack bracket is required. See page 47 for the available brackets

FLIGHTCASE LIFTOMATIC® SYSTEMS, A PERFECT RENTAL SYSTEM

Built-in lift system

Power supply

Power supply

Ref.

Ref.

Power supply: 230 VAC 50-60 Hz



Ref.FLM-5321Flightcase dimensions in mmcustom, depends on screen sizePresentation height (centre screen)1890 mm

Max. mounting range in mm. W 810 x H 446

Built-in lift system P5321 single column lift, page 95

FLM-5369

Flightcase dimensions in mm custom, depends on screen size

Presentation height (centre screen) 1890 mm

Max. mounting range in mm. W 810 x H 446

P5369 <u>double</u> column lift, page 95



90

90

100





LIFTOMATIC® WITH RETRACTABLE WHEEL SYSTEM, IDEAL FOR STUDIO USE



See page 47 for the available brackets

Ref.FSW-W85Dimensions in mmW 900 x D 700 x H 1875-1971Presentation height (centre screen)Continuously adjustableWheel adjustment in mm95,5Mounting interfaceL&S 5



230 VAC 50-60 Hz

Dimensions in mm
Presentation height (centre screen)
Wheel adjustment in mm
Mounting interface

95,5

L&S 5 230 VAC 50-60 Hz

approx 1000 - 1600 mm

W 900 x D 700 x H 1875-1971

▲ Perfect studio unit▲ High grade finishing

Adjustable presentation height
Electric retractable wheels

LIFTOMATIC® RENTAL SYSTEMS

ACCESSORIES

